



STANDARD SPECIFICATIONS

Performance

Max Capacity	1.600-kg
Max Lifting Height	3.0-m / 4.5-m
Dimensions (LxWxH) (mm)	3260 x 1100 x 2130 mm
Boom Angle	+10°/-5°
Turning Radius (mm)	1860 mm
Weight	2.200-kg
Wheelbase	1580 mm
Track Width	960 mm
Ground Clearance	100 mm
Gradeability	12 %
Driving Speed	11.0 km/h

Power Source

Electrical System	60V DC
Batteries	30 x 2V, 140 amp-hr
Drive Motor	Single Electric Traction

Tires

Standard Black Tires*
*Optional Non-Marking

KEY SPECS

Max Capacity
1.600-kg

Fork Size
1070 x 100 x 40 mm

Dimensions (LxWxH)
3260 x 1100 x 2130 mm

Max Lifting Height
3.0-m / 4.5-m

KEY FEATURES

- Maximum maneuverability by moving over uneven surfaces with Automatic Traction Control.
- Achieve optimum productivity with longer duty cycles.
- Produces zero emissions, 100% environmentally friendly.

ACCESSORIES & OPTIONS

- Blue Spot
- Red Lines
- Cabin
- Rotating Forks
- Fork Positioners
- Side Shift
- ATEX Conversions 