

# Warrior 1400X



The Powerscreen® Warrior 1400X is a flexible screening machine, aimed at small to medium sized operators who require a high performing, heavy duty, versatile machine that remains easy to transport. It offers improved performance, lower operating costs, and easier serviceability while building on the reliable foundation of our class-leading Warrior 1400 scalper. Its highly aggressive screen can accept bofor bars, finger screens, woven mesh and punch plates.

User benefits include jack up screen facilities to aid media access and hydraulic screen angle adjustment.

### Features & Benefits

- Heavy duty, incline belt feeder with hydraulic hopper sides
- Heavy duty, adjustable angle, grease lubricated 2 bearing, 2 deck screen box
- Jack up screen facility to aid mesh changes
- Screen walkway and access steps
- Hydraulic folding conveyors with excellent stockpiling capacity
- Engine protection shutdown system
- Improved stockpiling capacity
- Rapid set-up and shutdown time
- Two speed tracks
- Collection conveyor raise feature

### Options

- Radio controlled tracking
- Dual power (additional electric hydraulic drive)
- Quick release screen wedge tensioning
- Auto lubrication system
- Dust suppression
- Wide range of screen media
- 2 or 3 way split configuration
- High capacity incline apron feeder
- 300mm (12") Chassis riser
- Telescopic side conveyors
- Hopper extensions
- Screen blanket



Output Potential: up to 500 tph (551 US tph)

Warrior 1400X (Incline Belt Feeder)	3 Way Split
Weight (Est)	27,500kgs (60,627lbs)
Transport width	2.75m (9')
Transport length	14.21m (46'7")
Transport height	3.2m (10'6")
Working width	12.59m (41'3")
Working length	14.20m (46'7")
Working height	4.57m (15') (hopper extended)
	4.87m (16') (hopper extended, 300mm (12") riser)
Screen unit	3.6m x 1.25m (12' x 4.5')

