


MGTP

10000-55 1 PH

COMPACT LINE

power and innovation



engine



STAGE 5
CERTIFIED



Constructions



Mining operations



Events



Military applications

FEATURES

- ✓ 9.8kVA - 1-PH alternator
- ✓ Kubota diesel engine (Stage 5): World class performance, 1500rpm and water cooled
- ✓ HVO (Hydrotreated Vegetable Oil) fuel approved
- ✓ Emergency stop button
- ✓ Central lifting eye
- ✓ Engine protection shutdown system
- ✓ Extremely compact
- ✓ Extra-large base fuel tank
- ✓ Heavy duty and proven reliability
- ✓ Sustainable to run off either diesel or HVO
- ✓ To enable extremely long run time
- ✓ 28 hours @ 75% loads
- ✓ Shut down in the case of low fuel, low oil pressure, and battery charge failur

Dimensions

L x W x H (mm)	1332x825x1325
Weight (Kg)	490 (dry weight)

Technical Data

Fuel Tank Capacity (l)	55
Running time at 75% load (h)	28

Generator

Type	Meccalte PE28 2VS/4
Power	9.8 kVA / 7.8 kW
Frequency	50 Hz

Engine

Type	KUBOTA D1105 (STAGE V)
Cylinders	3
Power	13.7 HP
Engine speed (r.p.m.)	1500 r.p.m
Cooling	Water
Fuel	Diesel
Starting system	Electric

On board control panel equipped with:

DSE 3110 logic controller	2 shuko sockets 230V-16A
remote start/stop connector	1 socket CE 230V-16A
	1 socket CE 230V-32A



easy handling & transportability



TRIME

Sales Dept. +39 0382 406 252 - www.trime.it - info@trime.it

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.