

CUBE ⁺		SUPER 4x300W 24 V—LED	ECO 4x230W 24 V—LED	HYBRID 4x150W 24 V—LED	TRADITION 4x1000W 230V—MH
1 Cylinder dieselmotor (3000 RPM—AC)	Yanmar L70	OPTIONEEL (1C4x300L)	STANDAARD (1C4x230L)	-	-
2 Cylinder dieselmotor (1500 RPM—LC)	Kohler * KDW702	STANDAARD (2C4x300L)	OPTIONEEL (2C4x230L)	-	-
3 Cylinder dieselmotor (1500 RPM—LC)	Kubota D1105	-	-	-	STANDAARD (3C4x1kMH)
1 Cylinder dieselmotor 1 accu-pack	Yanmar L70	-	-	STANDAARD (1CH4x150L)	-

* Dieselmotoren kunnen zonder aankondiging worden gewijzigd naar Mitsubishi L2 of Kubota Z482.

Wij informeren u graag over de beschikbaarheid en details.

TECHNISCHE GEGEVENS

		SUPER (Std) (2C4x300L)	SUPER (Opt) (1C4x300L)	ECO (Std) (1C4x230L)	ECO (Opt) (2C4x230L)	HYBRID (1CH4x150L)	TRADITION (3C4x1kMH)
Bediening lichtmast	-	Hydraulisch	Hydraulisch	Hydraulisch	Hydraulisch	Hydraulisch	Hydraulisch
Afmetingen ingeschoven	cm	122 x 115 x 242	122 x 115 x 242	122 x 115 x 242	122 x 115 x 242	122 x 115 x 242	122 x 115 x 242
Afmetingen uitgeschoven	cm	179 x 174 x 840	179 x 174 x 840	179 x 174 x 840	179 x 174 x 840	179 x 174 x 840	179 x 174 x 840
Leeg gewicht	kg	1074	1045	1045	1074	1180	1060
Lampen (wattage)	W	4 x 300	4 x 300	4 x 230	4 x 230	4 x 150	4 x 1000
Lampen (type)	-	LED	LED	LED	LED	LED	Gasontladinglampen (MH)
Verlichtingsoppervlakte (5 lux min.)	m2	3900	3900	3000	3000	2300	4000
Lumen	lm	146000	146000	114000	114000	61000	360000
Roteerbaarheid lichtmast	°	340	340	340	340	340	340
Branduren lampen op accu's	h	-	-	-	-	9	-
Oplaadtijd accu's	h	-	-	-	-	5	-
Uitgaande voedingsconnector	-	2,5 kVA - 230 V	2,5 kVA - 230 V	2,5 kVA - 230 V	2,5 kVA - 230 V	2,5 kVA - 230 V	3 kVA - 230 V
Generator	-	5 kVA - 230 V	5 kVA - 230 V	5 kVA - 230 V	5 kVA - 230 V	5 kVA - 230 V	8 kVA - 230 V
Dieselmotor	-	2 cyl @1500RPM	1 cyl @3000RPM	1 cyl @3000RPM	2 cyl @1500RPM	1 cyl @3000RPM	3 cyl @1500RPM
Koeling dieselmotor	-	Watergekoeld	Luchtgekoeld	Luchtgekoeld	Watergekoeld	Luchtgekoeld	Watergekoeld
Inhoud brandstoftank	Liter	170	170	170	170	170	170
Aktieradius dieselmotor	h	170	325	325	170	700	100
Geluidsniveau	Lwa	83	90	90	83	0 - 90	88

Modificaties ter verbetering kunnen zonder nadere aankondiging worden toegepast door de producent.

GENERAC® | **MOBILE
PRODUCTS**

Generac Mobile Products Srl
 Part of Generac Power Systems, Inc.
 Via Stazione, 3 bis - 27030 Villanova d'Ardenghi (PV) - Italy
 Tel +39.0382.567011 - gmp.srl@generac.com
www.towerlight.com | www.generacmobileproducts.com