



HONDA

engine
Gasoline


MANUAL START
ENGINE
3000 r.p.m.



LWA
2000/14/CE



MGTP
6,5 H B M A S



MGTP
7 H B T A S



Code	PP61-7M00	P62-7T00
On board control panel equipped with:	- Hour counter - Volt meter - Main circuit breaker - 1x32A 1ph 230V EEC socket - 1x16A 1ph 230V EEC socket	- Hour counter - Volt meter - Main circuit breaker - 1x32A 3ph 400V EEC socket - 1x16A 1ph 230V EEC socket
Generator		
Type	Linz E1C10MH	Linz E1S10MH
Power	6,5 kVA 230V	7 kVA 400V
Frequency	50 Hz	50 Hz
Engine		
Engine type	HONDA GX390	HONDA GX390
N° cylinders	1	1
Power	11 HP	11 HP
Engine speed	3000 r.p.m.	3000 r.p.m.
Cooling	Air	Air
Fuel	Unleaded gasoline	Unleaded gasoline
Starting system	Manual recoil	Manual recoil
Technical Data		
Fuel tank capacity (l)	6,4	6,4
Running Time (h)	2	2
Dimensions		
Dimensions (LxW xH) mm	760 x 520 x 620	760 x 520 x 620
Weight (Kg)	91	91
Options	Trolley	Trolley



easy handling & transportability



TRIME®

Sales Dept. +39 0382 406 252 - www.trime.it - info@trime.it

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.