

COMPACT LINE

power
and innovation

STAGE 5
CERTIFIED

300 L
Fuel Tank
capacity

**designed and created
for your needs**

Designed to provide
an exceptional level
of performance
for every work on site
ensuring the right
balance between power
and ease of use

MGTP

10000-300 1 PH




**more sustainable
and environmentally
friendly future**

 **TRIME**[®]
Power Division

MGTP

10000-300 1 PH

power
and innovation

engine



APPLICATIONS



Constructions



Mining operations



Events



Military applications

FEATURES

- ✓ 9.8kVA (230V only) AC Aux Power
- ✓ Kubota diesel engine (Stage 5): World class performance, 1500rpm and water cooled
- ✓ HVO (Hydrotreated Vegetable Oil) fuel approved
- ✓ Emergency stop button
- ✓ Central lifting eye
- ✓ Engine protection shutdown system
- ✓ Extremely compact
- ✓ Extra-large base fuel tank
- ✓ Heavy duty and proven reliability
- ✓ Sustainable to run off either diesel or HVO
- ✓ To enable extremely long run time
- ✓ 157 hours @ 75% loads
- ✓ Shut down in the case of low fuel, low oil pressure, and battery charge failur
- Option for a remote start/stop connector

Dimensions	
L x W x H (mm)	1115x800x1560
Weight (Kg)	615 (dry weight)
Technical Data	
Fuel Tank Capacity (l)	300
Running time at 75% load (h)	157
Generator	
Type	Zanardi PE28 2VS/4
Power	9.8 kVA / 7.8 kW
Frequency	50 Hz
Engine	
Type	KUBOTA D1105 (STAGE V)
Cylinders	3
Power	13.7 HP
Engine speed (r.p.m.)	1500 r.p.m
Cooling	Water
Fuel	Diesel
Starting system	Electric
On board control panel equipped with:	
DSE 3110 logic controller	2 shuko sockets 230V-16A
	1 socket CE 230V-16A
	1 socket CE 230V-32A



easy handling & transportability



TRIME®

Sales Dept. +39 0382 406 252 - www.trime.it - info@trime.it

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.