

Perkins 2206C-E13TAG2 Diesel Generator Set



PRIME POWER

363 kVA / 290 kW

STANDBY POWER

400 kVA / 320 kW

Specifications

Voltage / frequency	400/230 V, 50 Hz
Power factor	0,8
Rated current	523 A
Model name	P400
Engine	Perkins 2206C-E13TAG2
Alternator	Leroy Somer TAL-A46-H
Control panel	DSE 7320
Fuel type	Diesel
Autonomy at 75% load	10,0 h
Dimensions	416 x 160 x 215 cm
Weight	4.550 kg

Ratings definitions

PRIME POWER PRP

Prime power available in variable load application in accordance with ISO 8528. A 10% overload capacity is available for a period of 1 hour within a 12-hour period of operation. Average power consumption should not exceed 80% PRP for each 24 h of work.

STANDBY POWER ESP

Emergency standby power rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload allowed; limited to 500 operating hours per year and 300 operating hours of continuous duty.

STANDARD REFERENCE CONDITIONS

Output ratings are presented at 25 °C air inlet temperature, barometric pressure 100 kPa and relative humidity 30%. This generating set is designed to operate at high ambient temperatures (up to 50 °C), humidity (up to 70%) and higher altitudes. Under specific site conditions, genset output power may derate.

Directives, Standards & Certifications

Category	References
EU Directives	2006/42/EC, 2014/30/EU
Product standards	EN 60204-1:2018, EN ISO 12100:2010, EN 55012:2007+A1:2009, EN ISO 8528-13:2016, EN 61000-6-1:2019, EN IEC 61000-6-4:2019
Manufacturer certifications	ISO 9001:2015 / GB/T 19001-2016, ISO 14001:2015 / GB/T 24001-2016, ISO 45001:2018 / GB/T 45001-2020



Technical Data

Engine

Model	2206C-E13TAG2
Brand	Perkins
Number of cylinders	6
Aspiration	in-line, turbocharged, air to air chargecooled
Fuel system	Direct injection
Displacement	12,5 L
Bore x stroke	115x149 mm
Compression ratio	16.3:1
Rated speed	1500 r/min
Rotation	Anti-clockwise, viewed on the flywheel
Engine power	305 kWm
Emission standard	Fuel Optimised (non-Stage V)
Coolant capacity	51,4 L
Oil capacity	40 L
Recommended oil	Perkins 15W-40 API CI-4

Alternator

Model	TAL-A46-H
Alternator brand	Leroy Somer
Phase	3
Voltage	400 V
Wiring type	6 wires
Bearing	1
Power factor	0,8
Frequency	50 Hz
Prime power	365 kVA
Excitation type	Brushless, self-excitation
Voltage regulation	±0,5 %
Protection grade	IP 23
Insulation class	H

Fuel consumption

110% load (Standby power)	82 L/h
100% load (Prime power)	75 L/h
75% load (Prime power)	58 L/h
50% load (Prime power)	40 L/h
Fuel capacity	580 L

Warranty

12 months from date of purchase or 1000 hours.

Features & Control

Standard features

Radiator (50 °C max.), belt-driven fan

24 V charging alternator

Single-bearing alternator, IP23

Insulation class H/H

Standard automatic control system

Main line circuit breaker / ACB

Base fuel tank

24 V batteries, rack and cables

Exhaust system

User manual

Battery charger

Jacket water heater

Controller

Model: DSE 7320

7 configurable digital inputs

Built-in governor and AVR control

Base load (kW export) functionality

Mains (utility) de-coupling protection

Generator power (kW, kVA) monitoring

Overload (kW & kV Ar) protection

Emergency stop

Start failure

