



Weidemann T 7042 telescopic loader

Engine

**Perkins 4-cylinder diesel engine, STAGE V, 122
hp**

Operating mass, kg	7 650 kg
Load capacity	4 200 kg
Carrying capacity max. Height	2 500 kg
The lifting height of the cargo in the bucket	7 305 mm
pagr. Point	6 825 mm
Mack. paeling height with pallet forks	6 230 mm
Landing height	
Dimensions (g x w x h), in standard equipment	4 950 x 2450 x 2425
Movement mechanism	Hydrostatic all-wheel drive
Working hydraulics	138.6 l/min, 261 bar
Transport Hydraulics	500 bar
Standard tyres	Mitas 405/70 R24 MPT-01
Travel speed, (km/h)	0-20 km/h
Hitch	Manitou coupling, mechanical
Standard equipment	ROPS/FOPS cab with heating and ventilation, VSG safety glass on the right, windshield wipers (also roof glass), adjustable steering column, cushioned armrest on the seat, 7-inch display, bottle holder, small compartments, comfort seat, traffic lights, LED work lights (1+1), electric hydr. parking brake, 3 steering modes, electric joystick with direction change switch and telescope shift function, VLS – Vertical lifting system, additional hydro outlet, reverse signal

Complete with optional equipment:

Code	Name
1000456819	Weidemann T 7042
CCA_SEAT_076	Seat with pneumatic suspension
CCA_HVAC_003	Conditioner
CCA_RADIO_002	Radio blank1
CLI_WRKLGTF_013	2x extra Led work light in front of
CLI_BEACON_010	Beacon
CRD_PLTBRCKT_002	Room holder
CEN_ENGINE_328	Engine 136 hp, Perkins, 550 Nm
CEN_FAN_003	Reversible fan
CDT_SPEED_036	40 km/h Power drive
CCT_TIRES_342	Firestone 460/70 R24 Duraforce
CFT_ADAPATT_021	Manitou hydr. Hitch
CGL_PACK_02_007	Boom damping + floating position + cylinder block.
CRD_SCKTRATT_002	Electrical outlet at the rear
CHY_PRELEASE_010	3. Hydration. Functions Pressure release button on the front
CHY_HIGHFLOW_002	High-power working hydr. Pump 187 l/min
CSM_TOOLBOX_002	Toolbox
CBS_BOOMSCR_002	Sagittarius telescope mudguard
CDT_DIFFLOCK_003	Diff. Mechanism lock for 100% front axle
CSM_SERCOVR_002	Central tunnel guard

CHI_HITCH_003	Automatic trailer hook 
CCA_HITCMIRR_002	Mirror for connecting a trailer

The loader is located in Latvia

Engine - Perkins 4-cylinder diesel engine, STAGE V, 136 hp ; Operating mass - 7, 650 kg; Carrying capacity max. - 4 200 kg; The lifting height of the cargo in the bucket pagr. at point - 7305 mm; Dimensions (g x w x h), in standard equipment 4 950 x 2450 x 2425; Hydrostatic all-wheel drive; Working hydraulics - 187 l/min, 261 bar; Transport hydraulics - 500 bar; Tires - Firestone 460/70 R24 Duraforce; Travel speed, (km/h) 0-40 km/h ; Manitou coupling, 100% front axle differential lock; ROPS/FOPS cab with heating and ventilation and air conditioning, VSG safety glass on the right, windshield wipers (also roof glass), adjustable steering column, damped arm support on the seat, 7-inch display, bottle holder, small compartments, comfort seat, traffic lights, LED work lights (1+1), electric hydr. parking brake, 3 steering modes, electric joystick with direction change switch and telescope shift function, VLS – Vertical lifting system, additional hydro outlet, reverse signal.

Complete with:

1.	Lightweight material bucket, with replaceable cutting edge, width 2500 mm, volume 3 m3, Manitou connection	
2.	Pallet forks, length 1200 mm, load capacity 5500 kg, Manitou connection	