

ENGINE SPEED (rpm):	1500	RATING STRATEGY:	STANDARD
COMPRESSION RATIO:	11.3	PACKAGE TYPE:	WITHOUT RADIATOR
AFTERCOOLER TYPE:	SCAC	RATING LEVEL:	CONTINUOUS
AFTERCOOLER - STAGE 2 INLET (°F):	90	FUEL:	NAT GAS
AFTERCOOLER - STAGE 1 INLET (°F):	198	FUEL SYSTEM:	CAT LOW PRESSURE
JACKET WATER OUTLET (°F):	210		WITH AIR FUEL RATIO CONTROL
ASPIRATION:	TA	FUEL PRESSURE RANGE(psig): (See note 1)	1.5-5.0
COOLING SYSTEM:	JW+OC+1AC, 2AC	FUEL METHANE NUMBER:	80
CONTROL SYSTEM:	ADEM3	FUEL LHV (Btu/scf):	905
EXHAUST MANIFOLD:	DRY	ALTITUDE CAPABILITY AT 77°F INLET AIR TEMP. (ft):	978
COMBUSTION:	LOW EMISSION	POWER FACTOR:	0.8
NOx EMISSION LEVEL (mg/Nm3 NOx):	350	VOLTAGE(V):	380-11000

RATING	NOTES	LOAD	100%	75%	50%
GENSET POWER (WITHOUT FAN)	(2)(3)	ekW	2000	1500	1000
GENSET POWER (WITHOUT FAN)	(2)(3)	kVA	2500	1875	1250
ENGINE POWER (WITHOUT FAN)	(3)	bhp	2789	2089	1398
GENERATOR EFFICIENCY	(2)	%	96.2	96.3	95.9
GENSET EFFICIENCY(@ 1.0 Power Factor)	(4)	%	39.7	38.5	36.7
THERMAL EFFICIENCY (ISO 3046/1)	(5)	%	45.8	47.1	48.8
TOTAL EFFICIENCY (@ 1.0 Power Factor)	(6)	%	85.5	85.6	85.5

ENGINE DATA						
GENSET FUEL CONSUMPTION	(ISO 3046/1)	(7)	Btu/ekW-hr	8683	8919	9354
GENSET FUEL CONSUMPTION	(NOMINAL)	(7)	Btu/ekW-hr	8895	9136	9582
ENGINE FUEL CONSUMPTION	(NOMINAL)	(7)	Btu/bhp-hr	6379	6561	6852
AIR FLOW (77°F, 14.7 psia)	(WET)	(8)	ft3/min	5754	4383	3024
AIR FLOW	(WET)	(8)	lb/hr	25514	19432	13410
FUEL FLOW (60°F, 14.7 psia)			scfm	328	252	176
COMPRESSOR OUT PRESSURE			psi(abs)	47.0	35.6	24.5
COMPRESSOR OUT TEMPERATURE			°F	356	282	202
AFTERCOOLER AIR OUT TEMPERATURE			°F	97	95	95
INLET MAN. PRESSURE		(9)	psi(abs)	41.7	31.7	22.0
INLET MAN. TEMPERATURE	(MEASURED IN PLENUM)	(10)	°F	100	99	98
TIMING		(11)	°BTDC	32	32	32
EXHAUST TEMPERATURE - ENGINE OUTLET		(12)	°F	852	900	936
EXHAUST GAS FLOW (@engine outlet temp, 14.5 psia)	(WET)	(13)	ft3/min	15125	11946	8471
EXHAUST GAS MASS FLOW	(WET)	(13)	lb/hr	26407	20121	13892
MAX INLET RESTRICTION		(14)	in H2O	10.04	10.04	10.04
MAX EXHAUST RESTRICTION		(14)	in H2O	20.07	20.07	20.07

EMISSIONS DATA - EXHAUST OUT						
NOx (as NO2)	(NOMINAL)	(15)(16)	g/bhp-hr	0.75	0.76	0.79
CO		(15)(17)	g/bhp-hr	2.08	2.06	2.06
NMHC (mol. wt. of 15.84)		(15)(17)	g/bhp-hr	0.91	1.05	1.20
NMNEHC (VOCs) (mol. wt. of 15.84)		(15)(17)(18)	g/bhp-hr	0.61	0.70	0.80
HCHO (Formaldehyde)		(15)(17)	g/bhp-hr	0.50	0.52	0.54
CH4 (mol. wt. of 16.04)	(NOMINAL)	(15)(19)	g/bhp-hr	4.73	5.44	6.23
CO2	(NOMINAL)	(15)(19)	g/bhp-hr	372	380	395
EXHAUST OXYGEN	(NOMINAL)	(15)(20)	% DRY		9.7	9.6
LAMBDA		(15)(20)		1.78	1.76	1.74

ENERGY BALANCE DATA					
LHV INPUT	(21)	Btu/min	296486	228410	159700
HEAT REJECTION TO JACKET WATER (JW)	(22)(29)	Btu/min	34358	29519	24154
HEAT REJECTION TO ATMOSPHERE	(23)	Btu/min	12385	9819	7677
HEAT REJECTION TO LUBE OIL (OC)	(24)(29)	Btu/min	7051	6266	5305
HEAT REJECTION TO EXHAUST (LHV TO 77°F)	(25)(26)	Btu/min	100012	81672	59445
HEAT REJECTION TO EXHAUST (LHV TO 248°F)	(25)	Btu/min	71045	58611	42860
HEAT REJECTION TO A/C - STAGE 1 (1AC)	(27)(29)	Btu/min	15916	6440	239
HEAT REJECTION TO A/C - STAGE 2 (2AC)	(28)(30)	Btu/min	13026	9390	6012

CONDITIONS AND DEFINITIONS

Engine rating obtained and presented in accordance with ISO 3046/1. (Standard reference conditions of 77°F, 14.50 PSI barometric pressure.) No overload permitted at rating shown. Consult the altitude deration factor chart for applications that exceed the rated altitude or temperature.

Emission levels are at engine exhaust flange prior to any after treatment. Values are based on engine operating at steady state conditions, adjusted to the specified NOx level at 100% load. Tolerances specified are dependent upon fuel quality. Fuel methane number cannot vary more than ± 3 .

For notes information consult page three.

FUEL USAGE GUIDE

METHANE NUMBER	30	35	40	45	50	55	60	65	70	75	80
SET POINT TIMING	-	-	-	-	-	16	16	16	18	23	32
DERATION FACTOR	0	0	0	0	0	0.78	0.87	0.95	1	1	1

ALTITUDE DERATION FACTORS AT RATED SPEED

INLET AIR TEMP °F	130	0.95	0.91	0.88	0.84	0.81	0.78	0.75	0.72	0.70	0.67	0.64	0.62	0.59
	120	0.96	0.93	0.89	0.86	0.83	0.80	0.77	0.74	0.71	0.68	0.65	0.63	0.60
	110	0.98	0.94	0.91	0.88	0.84	0.81	0.78	0.75	0.72	0.69	0.67	0.64	0.61
	100	1	0.96	0.92	0.89	0.86	0.82	0.79	0.76	0.73	0.70	0.68	0.65	0.62
	90	1	0.98	0.94	0.91	0.87	0.84	0.81	0.78	0.75	0.72	0.69	0.66	0.64
	80	1	0.99	0.96	0.92	0.89	0.85	0.82	0.79	0.76	0.73	0.70	0.67	0.65
	70	1	1	0.97	0.94	0.90	0.87	0.84	0.80	0.77	0.74	0.71	0.69	0.66
	60	1	1	0.99	0.96	0.92	0.89	0.85	0.82	0.79	0.76	0.73	0.70	0.67
	50	1	1	1	0.97	0.94	0.90	0.87	0.83	0.80	0.77	0.74	0.71	0.68
		0	1000	2000	3000	4000	5000	6000	7000	8000	9000	10000	11000	12000
ALTITUDE (FEET ABOVE SEA LEVEL)														

AFTERCOOLER HEAT REJECTION FACTORS (ACHRF)

INLET AIR TEMP °F	130	1.28	1.33	1.33	1.33	1.33	1.33	1.33	1.33	1.33	1.33	1.33	1.33	1.33
	120	1.23	1.27	1.27	1.27	1.27	1.27	1.27	1.27	1.27	1.27	1.27	1.27	1.27
	110	1.17	1.21	1.21	1.21	1.21	1.21	1.21	1.21	1.21	1.21	1.21	1.21	1.21
	100	1.11	1.15	1.15	1.15	1.15	1.15	1.15	1.15	1.15	1.15	1.15	1.15	1.15
	90	1.05	1.09	1.09	1.09	1.09	1.09	1.09	1.09	1.09	1.09	1.09	1.09	1.09
	80	1	1.04	1.04	1.04	1.04	1.04	1.04	1.04	1.04	1.04	1.04	1.04	1.04
	70	1	1	1	1	1	1	1	1	1	1	1	1	1
	60	1	1	1	1	1	1	1	1	1	1	1	1	1
	50	1	1	1	1	1	1	1	1	1	1	1	1	1
		0	1000	2000	3000	4000	5000	6000	7000	8000	9000	10000	11000	12000
ALTITUDE (FEET ABOVE SEA LEVEL)														

FUEL USAGE GUIDE:

This table shows the derate factor and full load set point timing required for a given fuel. Note that deration and set point timing adjustment may be required as the methane number decreases. Methane number is a scale to measure detonation characteristics of various fuels. The methane number of a fuel is determined by using the Caterpillar methane number calculation.

ALTITUDE DERATION FACTORS:

This table shows the deration required for various air inlet temperatures and altitudes. Use this information along with the fuel usage guide chart to help determine actual engine power for your site. The derate factors shown do not account for the external cooling system capacity. The derate factors provided assume the external cooling system can maintain the specified cooling water temperatures at site conditions.

ACTUAL ENGINE RATING:

To determine the actual rating of the engine at site conditions, one must consider separately, limitations due to fuel characteristics and air system limitations. The Fuel Usage Guide deration establishes fuel limitations. The Altitude/ Temperature deration factors and RPC(reference the Caterpillar Methane Program) establish air system limitations. RPC comes into play when the Altitude/Temperature deration is less than 1.0 (100%). Under this condition, add the two factors together. When the site conditions do not require an Altitude/Temperature derate (factor is 1.0), it is assumed the turbocharger has sufficient capability to overcome the low fuel relative power, and RPC is ignored. To determine the actual power available, take the lowest rating between 1) and 2).

- 1) Fuel Usage Guide Deration
- 2) $1 - ((1 - \text{Altitude / Temperature Deration}) + (1 - \text{RPC}))$

AFTERCOOLER HEAT REJECTION FACTORS(ACHRF):

To maintain a constant air inlet manifold temperature, as the inlet air temperature goes up, so must the heat rejection. As altitude increases, the turbocharger must work harder to overcome the lower atmospheric pressure. This increases the amount of heat that must be removed from the inlet air by the aftercooler. Use the aftercooler heat rejection factor (ACHRF) to adjust for inlet air temp and altitude conditions. See notes (29) and (30) for application of this factor in calculating the heat exchanger sizing criteria. Failure to properly account for these factors could result in detonation and cause the engine to shutdown or fail.

INLET AND EXHAUST RESTRICTIONS FOR ALTITUDE CAPABILITY:

The altitude derate chart is based on the maximum inlet and exhaust restrictions provided on page 1. Contact factory for restrictions over the specified values. Heavy Derates for higher restrictions will apply.

NOTES:

1. Fuel pressure range specified is to the engine fuel control valve. Additional fuel train components should be considered in pressure and flow calculations.
2. Generator efficiencies, power factor, and voltage are based on standard generator. [Genset Power (ekW) is calculated as: Engine Power (bkW) x Generator Efficiency], [Genset Power (kVA) is calculated as: Engine Power (bkW) x Generator Efficiency / Power Factor]
3. Rating is without engine driven water pumps. Tolerance is (+)3, (-)0% of full load.
4. Genset Efficiency published in accordance with ISO 3046/1, based on a 1.0 power factor.
5. Thermal Efficiency is calculated based on energy recovery from the jacket water, lube oil, 1st stage aftercooler, and exhaust to 248°F with engine operation at ISO 3046/1 Genset Efficiency, and assumes unburned fuel is converted in an oxidation catalyst.
6. Total efficiency is calculated as: Genset Efficiency + Thermal Efficiency. Tolerance is $\pm 10\%$ of full load data.
7. ISO 3046/1 Genset fuel consumption tolerance is (+)5, (-)0% at the specified power factor. Nominal genset and engine fuel consumption tolerance is $\pm 2.5\%$ of full load data at the specified power factor.
8. Air flow value is on a 'wet' basis. Flow is a nominal value with a tolerance of $\pm 5\%$.
9. Inlet manifold pressure is a nominal value with a tolerance of $\pm 5\%$.
10. Inlet manifold temperature is a nominal value with a tolerance of $\pm 9^\circ\text{F}$.
11. Timing indicated is for use with the minimum fuel methane number specified. Consult the appropriate fuel usage guide for timing at other methane numbers.
12. Exhaust temperature is a nominal value with a tolerance of (+)63°F, (-)54°F.
13. Exhaust flow value is on a 'wet' basis. Flow is a nominal value with a tolerance of $\pm 6\%$.
14. Inlet and Exhaust Restrictions are maximum allowed values at the corresponding loads. Increasing restrictions beyond what is specified will result in a significant engine derate.
15. Emissions data is at engine exhaust flange prior to any after treatment.
16. NOx tolerances are $\pm 18\%$ of specified value.
17. CO, NMHC, NMNEHC, and HCHO values are "Not to Exceed" levels. NMHC, and NMNEHC do not include aldehydes.
18. VOCs - Volatile organic compounds as defined in US EPA 40 CFR 60, subpart JJJJ
19. CO2 tolerance is $\pm 2.5\%$. CH4 tolerance is $\pm 26.0\%$. Fuel methane number cannot vary more than ± 3 .
20. Exhaust Oxygen tolerance is ± 0.5 ; Lambda tolerance is ± 0.05 . Lambda and Exhaust Oxygen level are the result of adjusting the engine to operate at the specified NOx level.
21. LHV rate tolerance is $\pm 2.5\%$.
22. Heat rejection to jacket water value displayed includes heat to jacket water alone. Value is based on treated water. Tolerance is $\pm 10\%$ of full load data.
23. Heat rejection to atmosphere based on treated water. Tolerance is $\pm 50\%$ of full load data.
24. Lube oil heat rate based on treated water. Tolerance is $\pm 20\%$ of full load data.
25. Exhaust heat rate based on treated water. Tolerance is $\pm 10\%$ of full load data.
26. Heat rejection to exhaust (LHV to 77°F) value shown includes unburned fuel and is not intended to be used for sizing or recovery calculations.
27. Heat rejection to A/C - Stage 1 based on treated water. Tolerance is $\pm 5\%$ of full load data.
28. Heat rejection to A/C - Stage 2 based on treated water. Tolerance is $\pm 5\%$ of full load data.
29. Total Jacket Water Circuit heat rejection is calculated as: $(\text{JW} \times 1.1) + (\text{OC} \times 1.2) + (1\text{AC} \times 1.05) + [0.9 \times (1\text{AC} + 2\text{AC}) \times (\text{ACHRF} - 1) \times 1.05]$. Heat exchanger sizing criterion is maximum circuit heat rejection at site conditions, with applied tolerances. A cooling system safety factor may be multiplied by the total circuit heat rejection to provide additional margin.
30. Total Second Stage Aftercooler Circuit heat rejection is calculated as: $(2\text{AC} \times 1.05) + [(1\text{AC} + 2\text{AC}) \times 0.1 \times (\text{ACHRF} - 1) \times 1.05]$. Heat exchanger sizing criterion is maximum circuit heat rejection at site conditions, with applied tolerances. A cooling system safety factor may be multiplied by the total circuit heat rejection to provide additional margin.

FREE FIELD MECHANICAL & EXHAUST NOISE
MECHANICAL: Sound Power (1/3 Octave Frequencies)

Gen Power Without Fan	Percent Load	Engine Power	Overall	100 Hz	125 Hz	160 Hz	200 Hz	250 Hz	315 Hz	400 Hz	500 Hz	630 Hz	800 Hz
ekW	%	bhp	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)
2000	100	2789	119.8	78.3	96.1	89.9	94.0	97.8	101.9	105.1	103.3	103.5	104.2
1500	75	2089	118.3	77.1	94.7	88.6	93.0	95.6	99.8	104.3	101.7	102.2	101.9
1000	50	1398	115.3	75.1	92.2	87.5	90.5	93.5	97.1	97.8	100.0	100.2	100.1

MECHANICAL: Sound Power (1/3 Octave Frequencies)

Gen Power Without Fan	Percent Load	Engine Power	1 kHz	1.25 kHz	1.6 kHz	2 kHz	2.5 kHz	3.15 kHz	4 kHz	5 kHz	6.3 kHz	8 kHz	10 kHz
ekW	%	bhp	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)
2000	100	2789	107.3	107.6	107.8	106.7	106.0	105.9	105.3	105.4	105.0	115.5	104.2
1500	75	2089	106.1	105.2	105.0	104.0	104.4	104.8	104.1	104.9	110.2	112.9	99.4
1000	50	1398	105.1	103.9	103.1	102.3	103.5	103.9	102.1	105.0	108.2	98.8	99.1

EXHAUST: Sound Power (1/3 Octave Frequencies)

Gen Power Without Fan	Percent Load	Engine Power	Overall	100 Hz	125 Hz	160 Hz	200 Hz	250 Hz	315 Hz	400 Hz	500 Hz	630 Hz	800 Hz
ekW	%	bhp	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)
2000	100	2789	126.2	96.1	111.5	102.9	107.0	110.4	111.8	109.2	114.6	111.2	110.5
1500	75	2089	123.2	95.3	111.0	104.0	107.5	109.6	112.4	106.0	111.3	105.9	103.9
1000	50	1398	120.2	93.2	110.3	102.5	104.5	106.3	110.5	102.9	110.6	103.6	99.1

EXHAUST: Sound Power (1/3 Octave Frequencies)

Gen Power Without Fan	Percent Load	Engine Power	1 kHz	1.25 kHz	1.6 kHz	2 kHz	2.5 kHz	3.15 kHz	4 kHz	5 kHz	6.3 kHz	8 kHz	10 kHz
ekW	%	bhp	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)
2000	100	2789	110.7	113.8	114.5	114.0	114.2	112.7	111.3	114.9	114.9	113.0	115.9
1500	75	2089	107.0	106.5	108.7	108.2	110.0	108.6	109.1	112.4	113.7	111.5	113.3
1000	50	1398	103.7	101.3	104.8	104.8	106.3	105.7	106.3	109.7	110.5	107.5	106.5

SOUND PARAMETER DEFINITION:

Sound Power Level Data

Sound power is defined as the total sound energy emanating from a source irrespective of direction or distance. Sound power level data is presented under two index headings:

Sound power level -- Mechanical

Sound power level -- Exhaust

Mechanical: Sound power level data is calculated in accordance with ISO 3747. The data is recorded with the exhaust sound source isolated.

Exhaust: Sound power level data is calculated in accordance with ISO 6798 Annex A. Exhaust data is post-catalyst on gas engine ratings labeled as "Integrated Catalyst".

Measurements made in accordance with ISO 3747 and ISO 6798 for mechanical and exhaust sound level only. Frequency bands outside the displayed ranges are not measured, due to physical test, and environmental conditions that affect the accuracy of the measurement. No cooling system noise is included unless specifically indicated. Sound level data is indicative of noise levels recorded on one engine sample in a survey grade 3 environment.

How an engine is packaged, installed and the site acoustical environment will affect the site specific sound levels. For site specific sound level guarantees, sound data collection needs to be done on-site or under similar conditions.