



SPECIFICATIES	SPECIFICATIONS	EMV 220	EMV 300	EMV 450	EMV 550	
Slagkracht	Centrifugal force	220	300	450	550	kN
Max. toerental	Max. frequency	3.000	2.400	2.460	2.500	rpm
Excentrisch moment	Eccentric moment	2,3	4,6	6,9	8,2	kgm
Amplitude	Amplitude	12	14,7	14,2	13,7	mm
Min. olieflow	Min. oilflow	90	130	195	255	l/min.
Min. werkdruk	Min. pressure	280	280	270	280	bar
Gewicht	Weight	580	965	1.275	1.500	kg
Max. trekkracht	Max. pull up	7.500	15.000	15.000	22.500	kg
Graafmachine	Typical excavator	7-18	12-35	22-45	30-55	ton
Slangenset	Hydraulic hoses	2	2	2	2	mtr

OPTIES	OPTIONS
Transportframe	Transport stand
Vork en pen	Bracket with pin
Snelwissel	Quick exchange adapter
JIB verlengstuk	JIB extension
Buisklemmen	Casing clamps with beam
Extra kettingen	Additional steel chains
Hijsmiddelen	Ground release lifting shackles

foundiz
SALES | RENTAL | CONSULTANCY

Foundiz BV
Kroonstraat 1
4879AV Etten-Leur (NL)
T: +31 (0)76 220 1005