


MGTP**10000-55 3 PH****power
and innovation****APPLICATIONS**

Constructions



Mining operations



Events



Military applications

FEATURES

- ✓ 9.8kVA (230V only) AC Aux Power
- ✓ Kubota diesel engine (Stage 5): World class performance, 1500rpm and water cooled
- ✓ HVO (Hydrotreated Vegetable Oil) fuel approved
- ✓ Emergency stop button
- ✓ Central lifting eye
- ✓ Engine protection shutdown system
- ✓ Extremely compact
- ✓ Extra-large base fuel tank
- ✓ Heavy duty and proven reliability
- ✓ Sustainable to run off either diesel or HVO
- ✓ 28 hours @ 75% loads
- ✓ Shut down in the case of low fuel, low oil pressure, and battery charge failur

Dimensions	
L x W x H (mm)	1332x825x1325
Weight (Kg)	490 (dry weight)
Technical Data	
Fuel Tank Capacity (l)	55
Running time at 75% load (h)	28
Generator	
Type	Linz CPT 18 SB
Power	9.8 kVA / 7.8 kW
Frequency	50 Hz
Engine	
Type	KUBOTA D1105 (STAGE V)
Cylinders	3
Power	13.7 HP
Engine speed (r.p.m.)	1500 r.p.m
Cooling	Water
Fuel	Diesel
Starting system	Electric
On board control panel equipped with:	
DSE 7310 logic controller	2 shuko sockets 230V-16A
remote start/stop connector	1 CE socket 400V-32A

**easy handling & transportability****TRIME®**Sales Dept. +39 0382 406 252 - www.trime.it - info@trime.it

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.