



SANDVIK QE342e MOBILE SCALPER

TECHNICAL SPECIFICATION

The QE342e heavy duty, tracked mobile scalping screen is designed to meet the requirements of operators who need a high performing, versatile unit that is easy to operate and transport. Fitted with hybrid drive option, this model provides the flexibility to operate in diesel or electric mode for lower operating costs and reduced carbon footprint.

KEY BENEFITS

Reliability	<ul style="list-style-type: none"> - Premium components selected throughout for maximum durability - Proven reliability and high performance - Capable of operating in the most hostile environments - Heavy duty chassis designed to accommodate interchangeable side conveyors and compatible for 2-way or 3-way split configurations - Large capacity wear resistant hopper with one-piece hopper design to minimize set-up time - Feeder load sensing facility to prevent blockages and unnecessary downtime
Productivity	<ul style="list-style-type: none"> - Class leading open scalping area enabling it to deliver enormous rates of production - Heavy duty 16' x 5' / 4.70 x 1.50 m screen box with high speed and aggressive throw for optimum throughput - Large stockpiling capability through integrated hydraulic conveyors - User friendly PLC control system with sequential start-stop for speed and ease of set-up - Choice of screen media to suit a wide range of applications - Interchangeable side conveyors, which are compatible for 2-way or 3-way split operation - Quick to set-up and easy to transport, resulting in more uptime and higher productivity - Connected to Sandvik My Fleet with 7 year data subscription offering 24/7 fleet management, geo-fencing and remote operator support
Cost of ownership	<ul style="list-style-type: none"> - Latest generation fuel efficient engines provide maximum performance and cost efficiency - Reduced fuel consumption through optimized hydraulic system and reduced engine RPM - Well-proportioned fuel tank to maximize intervals between refueling - Hydraulic service intervals increased from 2000 hrs to 4000 hrs, subject to oil sampling - Hybrid "e" drive with electric plug-in to run in diesel or electric mode for lower operating costs
Safety	<ul style="list-style-type: none"> - Mandatory audible and visual warning for safe operation whilst tracking and start-up / shut down - Emergency stop buttons and conveyor pull stop cords around the plant for easy access during operation - Wireless radio handset and two speed control for safe tracking onsite - Wrap-around hydraulically operated maintenance platforms provide safe access for service and maintenance - Screen box jack up facility allows safe and easy access to the bottom deck for maintenance and media changes
Sustainability	<ul style="list-style-type: none"> - Hybrid "e" drive reduces carbon emissions and minimizes fuel handling onsite - Latest emissions compliant engine lowers environmental impact due to reduced fuel consumption, less operating noise and low emissions - 50% hydraulic fluid saving with extended service interval from 2,000 to 4,000 hours





KEY SPECIFICATIONS	QE342e
Hopper	
Width	2570 mm / 8' 4"
Length	4160 mm / 13' 7"
Capacity	7.0 m ³ / 9.1 yd ³
Type	Rigid one-piece hopper
Feeder	
Type	Steel apron or heavy duty belt
Width	1360 mm / 54"
Oversize conveyor	
Width	1400 mm / 55"
Length (crs)	6270 mm / 27' 2"
Discharge height	4000 mm / 13' 1"
Angle adjustable	16° to 24°
Side conveyor (midsize)	
Width	800 mm / 32"
Discharge height	4090 mm / 13' 5"
Side conveyor (fines)	
Width	800 mm / 32"
Discharge height	4300 mm / 13' 12"
Transfer conveyor	
Width	1200 mm / 47"

STANDARD SPECIFICATION

Light mast and cabinet lights
 Radio control tracks 2 speed
 Hydraulic folding walkways
 Stabilizing legs***
 Screen box maintenance platforms
 Toughflex belt****
 Variable speed feed conveyor****
 3 hydraulic folding discharge conveyors
 Variable speed feed conveyor
 My Fleet telematics

***Standard on Hybrid powerpacks only

****Standard with belt feeder

KEY SPECIFICATIONS	QE342e
Screen box	
Type	2 bearing
Decks	2 deck
Top deck	4700 mm x 1450 mm / 15' 5" x 4' 9" (6.8m ²)
Bottom deck	4200 mm x 1430 mm / 13' 9" x 4' 8" (6.0m ²)
Variable screen angle	11° - 17°
Tracks	
Length (centres)	3310 mm / 10' 10"
Width (shoe)	400 mm / 16"
Control	Radio / Umbilical
Power pack	
Engine	CAT C4.4 Stage 5 / T4F 98 kW / 132 hp CAT C4.4 Stage 3A constant speed 98 kW / 132 hp
Hybrid drive	2 (x 37 kW / 50 hp)
Diesel tank size	300 litres / 80 USG
Hydraulic tank size	400 litres / 106 USG
Transport dimensions	
Length	14.83 m / 48' 8"
Width	3.00 m / 9' 10"
Height	3.40 m / 11' 2"
Standard weight	30,067 kg / 66,286 lbs
Operating dimensions	
Length	15.44 m / 50' 8"
Width	14.55 m / 47' 9"
Height	4.48 m / 14' 8"
Performance	
Max feed size	600 mm ³ / 24"
Capacity (up to)	500 mtph / 551 stph *
Travel speed	0.8 km/h / 0.5 mph slow 1.5 km/h / 0.0 mph fast
Max incline / Side to side	20° / 10°

Note. All weights and dimensions are for standard units only

For option availability please speak with your local Sandvik representative

* Application specific. Please contact a Sandvik representative for clarification on specifications and options
 Sandvik reserves the right to make changes to the information on this data sheet without prior notification to users