

Agricultural trailer ZASLAW Version D-737-8



Specifications

Trailer laden mass (max, kg)	11200
Load capacity (kg)	8000
Trailer capacity (m3)	10,8
Inner length of the cargo box (mm)	4500
Inner width of cargo box (mm)	2420
Height (mm)	2250
Overall length (mm)	6990
Outer width (mm)	2550
Platform height (mm)	1210
Cargo box boards (mm)	500+500
Trailer crossbar (mm)	1800

Detailed standard specification

Frame:

- lightweight construction made of structural steel with increased strength S355J, twice sandblasted, degreased, and then painted with high-quality acrylic varnishes in graphite RAL 7021 color; frame made of double T-shaped profile.

Spicy:

- 2 axles with homologation up to 40 km/h,
- Parabolic springs,
- Automatic braking force adjustment

Braking system:

- Drum brakes,
- Handbrake

Wheels:

- Tires 400/60R15.5,
- Steel wheel rims

Pneumatic system:

- single-wire pneumatic braking system,
- Parking brake

Cargo box:

- Tripartite dumping
- Improved with steel sheet – thickness 5 mm,
- Front wall made of one metal sheet with a viewing window,
- Side edges made of steel sheet – 2.5 mm
- Opening drop-down sides, central disconnection (7 locks),
- Case painted green RAL 6002
- Grain hatch on the back with a lid,
- Seal between the side edges that prevents water from leaking into the box housing inside

Other equipment:

- Wheel wedge – 2 pcs.,
- Hydraulic cylinder with oil shut-off valve at the maximum deviation of the loading box to the rear at an angle of 500 and up to 470 at a lateral angle,
- Wheel keys
- Warning triangle,
- Drawbar loop diam. - 40 mm,
- Steps in the cargo box inside and outside,
- Mudguards for rear wheels
- Wiring system – 12 V,
- Electrical socket for the second trailer,
- Rear coupling hook

Additional equipment:

- Tarpaulin with frame construction
- Working platform on the front wall
- Mudguards for front wheels

The trailer is certified and registered by VTUA