

U10 Technical Specification

Basic parameters

Machine weight	1050 kg
Bucket capacity	0.02~0.026 m ³
Width of bucket	356 mm

Performance parameters

Engine model	Kubota D722
Emission Standard	Euro V / EPA Tier 4F / CN IV
Engine power	10.2kW / 2500 rpm
Max. Gradeability	30 °
Max. digging force of arm	5.4 kN
Max. digging force of bucket	10.4 kN
Traveling speed	3.0/1.5 km/h
Max. hauling force	22.5 kN
Slewing speed of platform	7.5~8.5 rpm

Operating parameters



Max. digging height	3110 mm
Max. digging depth	2000 mm
Max. digging radius	3465 mm
Max. digging radius on ground level	3420 mm
Max. dumping height	2130 mm
Min. slewing radius	1365 mm
Max. vertical digging depth	1030 mm

Transportation dimensions

Overall length	2985 mm
Overall width	750 mm
Overall height	2290 mm

Other Parameters

Width of undercarriage	750mm / 990 mm
Length of track	1365 mm
Width of track	180 mm
Minimum ground clearance	155 mm
Height between platform and ground	400 mm
Platform tail turning radius	565 mm
Length to center of rollers	1040 mm
Fuel tank capacity	11 L
Hydraulic oil tank capacity	12 L
Track gauge	570/810 mm
Working Pressure	P1=P2=17.2MPa
Flow rate	P1=P2=10.5 L/Min
AUX 1 Pressure/ Flow rate	17.2 MPa/21 L/Min
Arm length	900 mm
Boom length	1450 mm
Max. lifting height of the dozer blade	215 mm
Steering head angle	55°(L)/55°(R)



*Specifications are subject to change without prior notice .



CE EAC MINI EXCAVATOR

YUCHAI EXCLUSIVE SELLER SK/CZ
MAX-PERFORMANCE, S.R.O.



Address: Bzovík 184, 962 41 Bzovík
Email: info@yuchai-bagre.sk
Tel.: +421 907 075 414
Website: www.yuchai-bagre.sk

BILLING DETAILS:
IČO: 36024937
DIČ: 2021337802
IČ DPH: SK2021337802

Machine weight : 1050 kg | Engine model : Kubota D722
Bucket capacity: 0.02~0.026 m³ | Engine power : 10.2 kW/2500 rpm
Overall dimensions (L x W x H): 2985mm x 750mm x 2290 mm

U10

