

1 Unit LB 24 S/N 115.400

Scope of supply

Pos.	Description	Qty.	Price (EUR)
<u>Basic machine</u>			
1.0	Superstructure 320 kW diesel engine, stage IV/Tier 4F, without counterweight	1	
2.0	Superstructure counterweight 12 t (2 x 6,0 t)	1	
3.0	Undercarriage LB 24 - B6 telescopic with cable remote control	1	
4.0	Crawler pads B6, 800 mm, 3-web grousers	1	
5.0	Painting in Liebherr-design	1	
6.0	Tool set standard	1	
<u>Economy and ecology</u>			
7.0	Eco-Silent Package	1	
<u>Leader system</u>			
8.0	Leader basic unit LB 24 excl. upper part and top, system 600 mm	1	
9.0	Leader upper part, machine height 22,8 m, system 600 mm	1	
10.0	Leader top, drill axis 1100 mm, system 600 mm	1	
11.0	Leader foot section standard foldable, system 600 mm	1	
12.0	Leader foot hydraulic, system 600 mm	1	
13.0	Kelly winch 20 t with hydraulic pull off function, 28 mm	1	
14.0	Crowd winch, push/pull force 32 t	1	
15.0	Auxiliary winch 8 t, 20 mm	1	
16.0	Litronic load indicator for kelly winch	1	
17.0	Litronic load indicator for crowd system	1	
18.0	Litronic load indicator for auxiliary winch	1	
19.0	Litronic working depth indicator for kelly winch	1	
20.0	Litronic working depth indication for crowd system	1	
21.0	Hook (single) 10 t, with chain	1	
<u>Application package</u>			
22.0	3-winding limiter for one winch	1	

Pos.	Description	Qty.	Price (EUR)
<u>Rotary drive related equipment</u>			
23.0	Single rotary BAT 270, automatic gear, excl. shock absorber	1	
24.0	Shock absorber for Kelly dia 419 mm, excl. driver unit	1	
25.0	Driver unit, dia 419 mm for single rotary BAT	1	
26.0	Cardan joint, dia 419 mm	1	
<u>Equipment for kelly drilling</u>			
27.0	Litronic operation mode kelly drilling	1	
28.0	Kelly bar swivel 25 t	1	
29.0	Litronic kelly visualization	1	
<u>Standard kellybar</u>			
30.0	Kelly bar 3-fold, locked type, 30 m, dia 419 mm sound insulated	1	
<u>LiDAT</u>			
31.0	LiDAT Plus incl. teleservice "Including the usage fee for the first year"	1	
<u>Self assembly features</u>			
32.0	Counterweight assembly device	1	
<u>Service package</u>			
33.0	Central lubrication superstructure and leader without sledge	1	
34.0	Central lubrication leader sledge	1	
35.0	Diesel refuelling pump electric	1	
36.0	Compressor for air tools	1	
<u>Optional safety features</u>			
37.0	Rear + side view camera, basic system	1	
38.0	Additional catwalks, foldable for transport	1	
39.0	Access ladder and platform for winch maintenance	1	
40.0	Handrails on rooftop, foldable	1	