

Kubota




LWA
2000/14/CE

WATER COOLED
ENGINE
3000 r.p.m.


MGTP

11 D AE




MGTP

12 D AE 3 f



MGTP

15 D AE 3 f



| Code | PP129-10MS0 | PP130-12TS0 | PP131-15TS0 |
|---------------------------------------|--|---|---|
| On board control panel equipped with: | <ul style="list-style-type: none"> - DSE ON/OFF switch - DSE 3110 module will display warnings, shutdowns & engine status information as high temperature, low oil pressure, low fuel level warning, Volts & Frequency, running hrs, battery voltage monitoring - Circuit breaker - Emergency stop - 2x32a 1ph 230v EEC socket - 1x16a 1ph 230v EEC socket | <ul style="list-style-type: none"> - DSE ON/OFF switch - DSE 3110 module will display warnings, shutdowns & engine status information as high temperature, low oil pressure, low fuel level warning, Volts & Frequency, running hrs, battery voltage monitoring - Circuit breaker - Emergency stop - 1x16A 3Ph 400V EEC socket - 1x32A 1Ph 230V EEC socket - 1x16A 1Ph 230V EEC socket | <ul style="list-style-type: none"> - DSE ON/OFF switch - DSE 3110 module will display warnings, shutdowns & engine status information as high temperature, low oil pressure, low fuel level warning, Volts & Frequency, running hrs, battery voltage monitoring - Circuit breaker - Emergency stop - 1x32A 3Ph 400V EEC socket - 1x16A 3Ph 400V EEC socket - 1x16A 1Ph 230V EEC socket |
| Features | <ul style="list-style-type: none"> •Soundproofed bodywork •Exhaust gas silencer •Remote boot connector | <ul style="list-style-type: none"> •Soundproofed bodywork •Exhaust gas silencer •Remote boot connector | <ul style="list-style-type: none"> •Soundproofed bodywork •Exhaust gas silencer •Remote boot connector |
| Generator | | | |
| Type | Linz E1C11M B | Linz E1S11M | Linz E1S13M C |
| Power | 11 kVA 230V | 12 kVA 400V | 15 kVA 400V |
| Frequency | 50 Hz | 50 Hz | 50 Hz |
| Engine | | | |
| Engine type | KUBOTA D722 | KUBOTA D722 | KUBOTA D1105 |
| N° cylinders | 3 | 3 | 3 |
| Power | 17 HP | 17 HP | 26 HP |
| Engine speed | 3000 r.p.m. | 3000 r.p.m. | 3000 r.p.m. |
| Cooling | Water | Water | Water |
| Fuel | Diesel | Diesel | Diesel |
| Starting system | Electric | Electric | Electric |
| Technical Data | | | |
| Fuel tank capacity (l) | 37 | 37 | 32 |
| Running Time (h) | 9 | 9 | 5,3 |
| Dimensions | | | |
| Dimensions (LxWxH)mm | 1220 x 670 x 840 | 1220 x 670 x 840 | 1410 x 700 x 870 |
| Weight (Kg) | 350 | 350 | 390 |
| Options | Trolley | Trolley | Trolley |



TRIME[®]

Sales Dept. +39 0382 406 252 - www.trime.it - info@trime.it