

Machine configuration: A4301463

	Key	Description
Homologationtype	3242	3242
machine no.	A4301463	A4301463
machine no.	A4301463	A4301463
	Unit type	Serial number
Gearbox	GBA25	F261349
Cabine	K08	X-2015001108
Motor	F4DFE414A*B001	001372076
Rearaxle	GPA54	F261552
Frontaxle	406013	40601301000867
Transmission	GTA2554	10020676
Equipment		
TH_102_4322	440/65 R28 Mitas AC 65 / fixed rim	
TH_102_4322	440/65 R28 Mitas AC 65 / fixed rim	
TH_103_59B2	520/70 R38 Mitas HC 70 / fixed rim	
TH_103_59B2	520/70 R38 Mitas HC 70 / fixed rim	
TH_105_0636	0636_21458900/2554	
TH_511_0001	0001_(W/o FL or frame)& OC	
TH_515_0002	0002_Sus.fr.axl.&Fr.Wei.block	
TH_517_0004	0004_High roof & 4 rear lights	
TH_538_0010	0010_Cab green bonnet	
TH_B02_0010	Front weight carrier 115 kg	
TH_B04_0000	Without linkage-mounted weight block	
TH_B06_0000	Without front PTO	
TH_B10_0000	Without front loader mounting bracket	
TH_B14_0000	Not relevant	
TH_B16_0000	Without bonnet protector bar	
TH_I02_0035	CIS, colour control terminal	
TH_I04_0040	Multifunction control lever for ELECTROPILOT + auto-shift	
TH_I10_0000	Without ISOBUS equipment	
TH_I12_0010	Additional operating panel for hydraulic functions	
TH_I22_0000	Not prepared for AUTO PILOT/GPS PILOT	
TH_I24_0000	Without SAT 900 GNSS receiver	
TH_I26_0000	Without TELEMATICS	
TH_I28_0000	Without terminal	
TH_J02_0060	Rear linkage, electrohydraulic, 5.75 t	
TH_J04_0300	Lower links, cat. 3 with hook	
TH_J06_0200	2x side stabilisers on lower link, mechanical	
TH_J08_0130	Top link, cat. 3/2 with hook	
TH_J10_1010	Pick-up hitch, hydraulic push out	
TH_J14_0000	Without drawbar	
TH_J16_0000	Without rear clevis	
TH_J18_0000	Without linkage drawbar and ball set	
TH_J40_0030	Hydraulic brakes.	
TH_K02_0091	Open centre hydraulics, 100 l/min	
TH_K04_0151	5 spool valves, 3 x mechanical, 2 x electrohydraulic (CIS)	

Equipment

TH_K10_0000	Without front hydraulic outlets
TH_K12_0000	Without Power Beyond
TH_N02_0010	QUADRISHIFT transmission
TH_N04_0200	Transmission ratio 40 km/h
TH_N06_0210	Front axle, PROACTIV with independent wheel suspension
TH_N08_0120	Rear axle, standard
TH_N10_0020	PTO: 540/540 ECO + 1000 rpm
TH_N14_0010	PTO stubs, 21 splines and 6 splines, 1 3/8"
TH_N22_0247	Front mudguards, pivoting, 470 mm
TH_N26_0020	Wheel spacers for rear axle (2 x 43 mm)
TH_N30_0010	PTO control, rear
TH_N32_0000	Without automatic PTO engagement/disengagement, rear
TH_N34_0000	Without rear wheel weights
TH_P02_0050	125 hp rated output, 130 hp max. output, ECE R 120
TH_P04_0010	Without diesel pre-filter
TH_P06_0030	Battery master switch, electronic
TH_P08_0020	White diesel
TH_P10_0010	Cold start kit down to -30 °C
TH_Q02_0010	6-pillar cab, high-/low-profile roof
TH_Q04_0200	High roof with hatch
TH_Q08_0020	Rear window wiper
TH_Q14_0020	Mirrors: 2 external, telescopic
TH_Q18_0010	Lateral mudguard extensions
TH_Q20_0000	Without screen mounting rail
TH_Q30_0000	Without additional interface sockets
TH_Q40_0030	2x high-level headlights on the roof, halogen
TH_Q44_0131	Work lights: 2 x bonnet, 2 x front, adjustable and 4 x rear
TH_R00_0000	Colour, CLAAS Green
TH_R04_0130	Driver's seat, fabric, air suspension
TH_R06_0020	Passenger seat with safety belt
TH_R08_0010	Air conditioning
TH_R10_0010	Preparation for radio
TH_R12_0020	Cooler compartment for 1.5 l bottle (under the instructor's seat)
TH_R20_0000	Without dynamic steering
TH_S02_0001	Sticker, standard
TH_S04_0010	Right-hand drive
TH_S06_0030	2x rotating beacons
TH_S08_0001	Equipment - European Union
TH_T02_0010	Truck transport
A43/200	ARION 450