

SCISSOR LIFTS DS1823RT



- ✓ 4X4 ALL WHEEL DRIVE
- ✓ GRADEABILITY 30%
- ✓ EXTENSION DECK
- ✓ NON-MARKING TIRES
- ✓ SOCKET IN BASKET
- ✓ SWING AXLE
- ✓ AUTOMATIC LEVELING
- ✓ SUPERDECK

TECHNICAL SPECIFICATIONS

Working height	18.00 m
Platform height	16.00 m
Length	4.88 m
Width	2.27 m
Height (Rails up)	3.19 m
Height (Rails down)	2.49 m
Platform length x width	3.98 m * 1.83 m
Platform extension	1.43 m / 1.16 m
Ground clearance	0.30 m
Wheelbase	2.86 m
Load capacity	680 kg
Load capacity on platform extension	227 kg
Max numbers of persons	6 Persons
Turning radius (inside / outside)	2.35 m / 5.20 m
Driving speed (retracted)	6.10 km/h
Driving speed (extended)	1.10 km/h bis 9 m
Weight	9,190 kg
Motor	Kubota V2403-M-DI 36.5 kW / 2,600 rpm
Hydraulic tank	130 Liter
Diesel tank	100 Liter



Disclaimer:

During the design and creation of this datasheet, we have worked with the utmost care. However, we cannot guarantee that the information in this datasheet is complete, current and/or accurate. No rights can therefore be derived from texts, specifications, images, or other information in this datasheet.