











Electric engine powered

APPLICATIONS



FEATURES

- Integrated control panel
- SMART START SYSTEM
- Emergency stop button
- Phase inverter
- Water pump
- Water pressure Gauge
- Water Safety pressure switch
- Manual water drain system
- Central lifting eye
- Forklift pockets
- Stainless steel crown with 24 nozzles
- Galvanized SKID base with forklift pockets

SAFETY

- Reduce dust for healty and safe environment
- Safety automatic clutch compliant with HSE norm
- Remote control with full operation
 - start/stop
 - tilt up/down
 - turn left/right/auto

OPTIONS

60 Hz

External pump for chemicals additives

R.O.T. SYSTEM

- Remote control, 50m range programmable function"cicle"
- Automatic oscillation 0 340° manual area setting
- Electric Tilting System

Electric engine power (kW)	7.5
Inlet plug	400V3P+N+T 50Hz 32A
Fan diameter (mm)	900
Water consumption (I/m)	37 - 43
Coverage (m)	30 - 40
Water connection	UNI 45 or STORZ or CAMLOCK
Max. water throw height (m)	10
Min. inlet Water pressure (bar)	1.0
Generator required (kVA)	15
Water inlet filter (Mesh)	60
Y Filter (µm)	500
Electric tilting system	0 - 35°
Automatic oscillation	0 - 340°
(working angle settable manualy)	manual area setting
Dimensions (mm)	1719x1345x2065
Weight (kg)	750



