




QUICK UP



ADAPTED TO EACH PROJECT

- > Its light weight makes it suitable for the most fragile grounds
- > Its compactness enables to go through doors and elevators
- > Its stabilizers with rubber protect the floor surface

EASY TO USE

- > Quick set up by 1 person
- > Transportable on a trailer or a van
- > 4 wheels for easy manual maneuvering

BEST VALUE FOR MONEY

- > Minimal maintenance

PUSH-AROUND

TECHNICAL DATA

	QUICK UP 8	QUICK UP 9	QUICK UP 11	QUICK UP 12	QUICK UP 14
Working height	8.1 m	9.5 m	10.8 m	12.3 m	13.7 m
B Platform height	6.1 m	7.5 m	8.8 m	10.3 m	11.7 m
Lift capacity	159 kg	159 kg	159 kg	136 kg	136 kg
Platform size	0.68 x 0.66 m	0.68 x 0.66 m	0.68 x 0.66 m	0.68 x 0.66 m	0.68 x 0.66 m
C Length	1.22 m	1.28 m	1.34 m	1.4 m	1.47 m
D Width	0.8 m	0.8 m	0.8 m	0.8 m	0.8 m
A Height - stowed	1.98 m	1.98 m	1.98 m	1.98 m	1.98 m
E Width - stabilised	1.55 m	1.55 m	1.55 m	2.06 m	2.34 m
F Length - stabilised	1.75 m	1.75 m	1.75 m	2.26 m	2.7 m
Energy (AC)	230 V	230 V	230 V	230 V	230 V
Weight (AC)	340 kg	360 kg	380 kg	415 kg	455 kg
Energy (DC)	12 V	12 V	12 V	12 V	12 V
Weight (DC)	382 kg	402 kg	422 kg	457 kg	497 kg

STANDARD EQUIPMENT

- > Easy to use thanks push button controls
- > Emergency control
- > Manual platform lowering valve
- > Integrated forklift pockets
- > Lifting eye
- > Non marking wheels
- > Harness attachment point
- > Lights on control box to confirm stabilizers are set

OPTIONS AND ACCESSORIES

- > 2 available versions: supply-power (AC) or battery (DC)

