

Machine configuration: 99401155

	Key	Description
machine no.	99401155	99401155
machine no.	99401155	99401155

Equipment

LW_B02_0670	CARGOS 9600
LW_C06_0020	Hydraulically folding cutting trough with central locking
LW_C08_0010	Mechanical knife pretension adjustment
LW_F02_0110	Rear section – side wall sections, factory-mounted
LW_F04_0110	Without metering roller drive
LW_F06_0020	Front flap at top, hydraulically folded
LW_F08_0960	Side height extension (load volume 50 m³)
LW_F12_0040	Additional parts, chassis for 26.5"/30.5" tyres
LW_I27_0050	TIM SPEED CONTROL
LW_I27_0500	Automated blockage clearance via sequential switching
LW_M02_0320	Articulated drawbar bottom hitch, maximum tongue load 4 t
LW_M04_0040	Double-wide-angle PTO drive shaft, 6-spline
LW_M06_0130	Ball hitch K80
LW_N04_0280	Forced steering, electrohydraulic
LW_N08_0660	Tridem axle, 30 t axle loading, with hydraulic suspension
LW_N09_0050	Suspension for hydraulic chassis
LW_N09_0110	Lift axle for front axle
LW_N10_0510	800/45 R26.5 Alliance tridem tyres
LW_N12_0120	Compressed air brake system for hydraulic suspension
LW_N14_0050	Brake cylinder for compressed air brake system, 30 t tridem axle
LW_N16_0080	Mudguards for external widths > 2.55 m, 30 t tridem axle
LW_Q05_0100	TONI – TELEMATICS ON IMPLEMENT
LW_Q06_0500	CEMIS 700
LW_Q07_0100	ISOBUS cable
LW_Q12_0020	Work lights
LW_R02_0020	Torque measurement in drive train for automatic loading function
LW_R03_0090	Control line for load-sensing system
LW_R03_0200	Load weight indicator
LW_R03_0210	Pick-up relief, hydraulically adjustable
LW_R03_0220	Auxiliary guide roller for pick-up, central position
LW_S02_0010	Statutory equipment, Standard
LW_S04_0030	Maximum permissible speed 60 km/h
LW_S06_0110	Technical documentation, Finnish
994/130	CARGOS 9600 TRIDEM