

LINDNER LINTRAC 130

Comfort cabin:	TracLink comfort cab, safety frame ROPS, green panoramic glazing, front loader transparency shop window, opening front, side and rear windows, passenger seat, interior trim, Grammer comfort seat (pneumatic spring) with document storage, LED cabin lighting with automatic switching on when opening the door, heating and ventilation system with 4-band high-performance blower, signal jack, start lock, DC socket (3-pole), interval windshield wiper, reset indicator, 12-volt telephone plug, sun visor and visor, conditioner, I.B.C - monitor PRO with remote control, cab damping (+2cm height) mechanical;
Engine:	136 hp (100 kW) ISO14396, 4-cylinder PERKINS 904J- E36TA Common rail, Particulate filter and SCR, 3.600cm³, 530 Nm at 1400 rpm, STAGE V , air filter with indicator, 12V system, Tank capacity: 140l + 19l AdBlue
Transmission and axles:	TMT11.2 - ZF-Continuously variable transmission, Lindner LDrive, 40 km/h, (50 km/h option), active parking brake , high-traction function, all-wheel drive control with button, rear diff. button locking, Power-shift rear PTO 430 / 540 / 750 / 1000 rpm , OPTION: LINDNER steering rear axle (up to 20 degrees) with 4 modes: reverse, crab, standard, manual;
Brakes:	Transmission braking function, Hdr. control rear wet multi-disc brakes with automatic force distribution (Optistop), steering brake, electro-hydraulic safety switch, option: 4-wheel shaft brakes, pneumatic brakes, hydr. trailer brakes
Hydraulics:	BOSCH-Rexroth hydro. system with variable volume pump, Automatic suspension control AHC with oscillation reduction, independent oil system, 3x proportional EHS valves with priority and flow regulation (load sensitivity), Multifunctional joystick on LDrive hand support, yield 4-88 l/min, 4 hydr. outlet lines + reflux, load capacity 4900 kg, option: higher load capacity
Lighting:	2 x H7 bi-halogen headlights (option: Bi-LED) , 2 x side indicators LEDs, LED daytime running lights, 2 x rear stop lights LED with integrated turn signal, 4 x LED headlights at the top, 2 x LED work lights (front and rear), LED position light at the rear
Standard equipment	Front balance bracket, quick connections at the top and bottom, valve protection, adjustable trailer coupling, air blower with filter at the rear of the cab, digital display, sliding rear window, air conditioning, quick connect top linkage, extra lifting cylinders, fuel consumption display, programmable hand throttle; electric mass switch, hydr. connections to oil drain reservoir, Lindner safety package, drink holder, TracLink Smart equipment recognition, stop button on the support.
Standard wheels:	440/65 R 24 front and 540/65 R 34 rear

Number	Name
--------	------

	Lintrac 130
L378C	TracLink Phone Holder
L384D	TracLink Smart telematics with equipment recognition and 5 smarttags
L40BE2	540/65-R34 Myth AC 65 - 440/65-R24 Myth AC 65
L172B	Rear axle, steering
L190C	Speed 50 km/h
L202B	Front axle damping
L342B	Heated windscreen
L380B	Signal socket
L382B	ISO-BUS socket
L480J	Adjustable python hook
L500D	front PTO and suspension 2500 kg
L550B	2 hydrs. in front of the line
L600D	Air brake two-circuit including anti-icing function + 1 line trailer hydr. brake valve
L640C	4 x EHS control units
L661B	Micro switches for 3 front loader
L720B	6 hydr. lines + reflux
L800E	Hauer front loader mount
L830D	Synchro-Lock mount
3020095	Hauer front loader TOP-BLOCK POM-LX 110, EURO mount
L665D	Valve 4th hydr. Function
L870B	hydr. locking mechanism
L980B	Engine preheating device

Lintrac 130

**Dimensions:**

Gross weight: 7200 kg
Unladen weight: 4520 kg
Wheelbase: 2375 mm
Height (C): 2610 mm
Width (W): 1978 mm
Length (A): 3681 mm

