

	Product Information		Slab Props For use as backpropping
	PI 235	7/7	Deckenstützen Einsatz beim Durchstützen von Decken

Permissible loads [kN] in case of backpropping without formwork
Zulässige Lasten [kN] beim Durchstützen von Decken ohne Schalung

extend. lenght [m] Auszugslänge [m]	MULTIPROP [kN]		
	MP 250	MP 350	MP 480
1,45	90,0		
1,50	90,0		
1,60	90,0		
1,70	90,0		
1,80	90,0		
1,90	90,0		
2,00	90,0	90,0	
2,10	90,0	90,0	
2,20	90,0	90,0	
2,30	90,0	90,0	
2,40	89,8	90,0	
2,50	88,0	90,0	
2,60		90,0	90,0
2,70		90,0	90,0
2,80		90,0	90,0
2,90		90,0	90,0
3,00		90,0	90,0
3,10		86,8	90,0
3,20		83,3	90,0
3,30		79,9	90,0
3,40		76,4	90,0
3,50		73,0	90,0
3,60			89,1
3,70			85,2
3,80			81,3
3,90			77,3
4,00			73,4
4,10			69,5
4,20			66,6
4,30			63,7
4,40			60,8
4,50			57,9
4,60			55,0
4,70			52,0
4,80			49,1

extend. lenght [m] Auszugslänge [m]	MULTI- PROP [kN]
	MP 625
4,30	81,4
4,40	79,1
4,50	76,8
4,60	74,5
4,70	72,2
4,80	70,0
4,90	67,7
5,00	65,4
5,10	63,2
5,20	60,9
5,30	58,7
5,40	56,4
5,50	54,2
5,60	51,9
5,70	50,1
5,80	48,3
5,90	46,5
6,00	44,6
6,10	42,8
6,20	41,0
6,25	40,1