Hyundai DP222LC

Diesel Generator Set

PRIME POWER	STANDBY POWER
750 kVA / 600 kW	**825 kVA / 660 kW**

Specifications

Voltage / frequency	400/230 V, 50 Hz
Power factor	0,8
Rated current	1082,6 A
Model name	D825
Engine	Hyundai DP222LC
Alternator	Leroy Somer TAL-A49-B
Control panel	DSE 7320
Fuel type	Diesel
Autonomy at 75% load	10,5 h
Dimensions	481 x 195 x 250 cm
Weight	6.185 kg

Ratings definitions

PRIME POWER PRP

Prime power available in variable load application in accordance with ISO 8528. A 10% overload capacity is available for a period of 1 hour within a 12-hour period of operation. Average power consumption should not exceed 80% PRP for each 24 h of work.

STANDBY POWER ESP

Emergency standby power rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload allowed; limited to 500 operating hours per year and 300 operating hours of continuous duty.

STANDARD REFERENCE CONDITIONS

Output ratings are presented at 25 °C air inlet temperature, barometric pressure 100 kPa and relative humidity 30%. This generating set is designed to operate at high ambient temperatures (up to 50 °C), humidity (up to 70%) and higher altitudes. Under specific site conditions, genset output power may derate.

Directives, Standards & Certifications

Category	References
EU Directives	2006/42/EC, 2014/30/EU
Product standards	EN 60204-1:2018, EN ISO 12100:2010, EN 55012:2007+A1:2009, EN ISO 8528-13:2016, EN 61000-6-1:2019, EN IEC 61000-6-4:2019
Manufacturer certifications	ISO 9001:2015 / GB/T 19001-2016, ISO 14001:2015 / GB/T 24001-2016, ISO 45001:2018 / GB/T 45001-2020

Technical Data

Engine

Model	DP222LC
Brand	Hyundai
Number of cylinders	12
Aspiration	Turbocharged and intercooled
Displacement	21,927 L
Bore x stroke	128 x 142 mm
Compression ratio	15,0:1
Rated speed	1500 r/min
Engine power	657 kWm
Coolant capacity	114 L
Oil capacity	40 L

Alternator

Model	TAL-A49-B
Alternator brand	Leroy Somer
Phase	3
Voltage	400 V
Wiring type	12 wires
Bearing	Single bearing
Power factor	0,8
Frequency	50 Hz
Prime power	750 kVA
Excitation type	Brushless, self-excitation
Voltage regulation	±0,5 %
Protection grade	IP23
Insulation class	H

Fuel consumption

110% load (Standby power)	177 L/h
100% load (Prime power)	161 L/h
75% load (Prime power)	119,1 L/h
50% load (Prime power)	79,3 L/h
Fuel capacity	1250 L

Warranty

12 months from date of purchase or 1000 hours.

Features & Control

Standard features

- Radiator (50 °C max.), belt-driven fan
- 24 V charging alternator
- Single-bearing alternator, IP23
- Insulation class H/H
- Standard automatic control system
- Main line circuit breaker / ACB
- Base fuel tank
- 2 x 12 V batteries, rack and cables
- Exhaust system
- User manual
- Battery charger
- Jacket water heater

Controller

- Model: DSE 7320
- 7 configurable digital inputs
- Built-in governor and AVR control
- Base load (kW export) functionality
- Mains (utility) de-coupling protection
- Generator power (kW, kVA) monitoring
- Overload (kW & kV Ar) protection
- Emergency stop
- Start failure

© 2026 DPX Power B.V. All rights reserved. Specifications, dimensions, features and technical data are subject to change without prior notice. Images and illustrations are for reference only and may differ from the actual product. Product configuration may vary depending on options and local requirements. All trademarks are the property of their respective owners.